COMPSCI 314 S1 C

IPv6, UDP, TCP ICMP, SSH, FTP

Network Byte Order

- Computers have many interesting and different conventions for the ordering of bits in bytes, bytes in words, and words in messages.
- To give a uniform interpretation within the network, the Internet Standards specify a *Network Byte Order* for all fields interpreted by the network.
- Integers within network headers must be sent with the bytes in decreasing numerical significance, most-significant byte first.
- (The most-significant byte is nearest the start of the packet.)
- This means that bytes or octets are transmitted in "raster-scan" order, left to right, top to bottom, as we look at the diagrams.
- User data may be converted to Network Byte Order at the choice of the user.

Bits within a byte are sent least-significant-bit first; see RFC 2469 for comments on this

IP Version 6 (IPv6)

[Shay 2nd Edition, pp 506-515]

IP Version 6 addresses several problems with the older IP (version 4), especially —

- Exhaustion of the 32-bit address space
- Fragmentation is difficult and expensive for routers
- The IPv4 header is too complex many aspects can be removed to specialised headers

Other new features include —

- Autoconfigration (site-local addresses)
- Encryption (of header fields and/or user payload)

The IPv6 Header



- The introduction is 64 bits long, and each address is two lots of 64 bits for better efficiency in fast processors
- The NEXT HEADER identifies either the header OR (on the last header) the packet protocol (e.g. TCP)

IPv6 Header Fields

 Hop Limit is set to the maximum number of hops and is decremented by each router. The packet is discarded if its hop limit becomes zero.
It is like the IPv4 'TIME TO LIVE' (as it eventually developed, not

as originally defined), but is not decremented by time.

- Flow Label is a unique identifier allocated by the source to a series of related packets. It allows packets to be treated similarly by routers, such as following the same paths. (The flow label and source address may be used to retrieve cached route information.) The flow label usually expires if not used for a while.
- Extension Headers are somewhat like IPv4 options. Each header (including the IPv6 header) indicates the nature of the next header, or the payload protocol if there are no more optional headers.
- Checksums are assumed to be handled by the underlying datalink layer and are omitted from the IPv6 header.

Notes on Checksums

TCP and IP were originally designed for unreliable links with poor error checking. They therefore have multiple levels of overlapping checksums. With Ethernet we get that



 TCP check covers whole of user data + TCP header for a complete end- to-end check, including source and destination addresses

- IPv4 check covers just the IP header to minimise switching overheads
- Ethernet check is very strong and covers all of each IP packet
- *IPv6 relies completely on the underlying checksums*

IPv6 Extension Headers

- IPv6 moves some information from the IPv4 header into extension headers which follow the main IPv6 header and have defined formats
- The IPv6 header has a 'next header' field which gives the type of the first header, and each header itself has a 'next header' field
- Header types are
 - Authentication
 - Destination options
 - Fragmentation
 - Hop-by-hop
 - Routing
 - Security

IPv6 Fragmentation

- IPv6 routers and switches do not fragment packets en route; the sender is supposed to ensure that the packet fits within the MTU for the path
- If a user packet is too long, the sender must fragment it and create appropriate smaller packets, each with an appropriate fragment header to allow reassembly of the user packet
- There is a way for IPv6s host to *discover* path MTUs
- Summary: fragmentation is entirely the responsibility of the *sender*

Connecting applications

- Data doesn't just get sent from host to host
- Data is exchanged between applications on the hosts concerned
- A typical host runs multiple applications simultaneously: WWW, e-mail, FTP, networked games, SSH or Telnet, database server/client, NetLogin, ...
- Problem: IP itself provides the means for routing between hosts, but not for routing between applications
- How do we indicate which application our IP packet's payload originates from, and which application it is intended for?
- Need a higher order protocol to sort this one out! E.g., UDP or TCP

The concept of ports

- These are 'addresses' or identifying numbers for users of UDP and TCP, just like protocols or access points at lower layers —
- The LLC layer uses the DSAP to select the service, say IP
- IP uses its protocol field to select a networklayer protocol such as TCP (or ICMP etc.)
- TCP uses the Destination Port to select the end-user service, e.g. FTP or e-mail. Similarly, the Source Port identifies the sending user application

More on ports

- TCP and UDP, the two most important protocols layered on top of IP, both implement 'ports'
- An (IP) 'port' identifies a sending or receiving application
- Port numbers in TCP and UDP are 16 bit, i.e., we can address up to 65536 applications on each host with each protocol
- Low-numbered ports (< 1024) are reserved for 'well-known' services, such as e-mail, web, ssh, etc.
- More on ports later!

UDP and TCP

- UDP and TCP datagrams are encapsulated inside IP datagrams
- UDP User Datagram Protocol: A connectionless best-effort protocol
- TCP *Transmission Control Protocol*: A connection-oriented reliable *byte* stream protocol
- UDP and TCP are 'end-to-end network-layer protocols' – the two hosts involved are solely responsible for header, content, error detection, error recovery, etc. Other hosts just forward the encapsulating IP datagram without looking at the content (at least in theory, anyway!)

User Datagram Protocol (UDP)

- UDP is used to send a single piece of information (byte block) from an application on one host to an application on another host via an agreed pair of ports
- Applications on each side are identified by their respective port numbers
- Delivery is 'best effort,' but not reliable lost datagrams are not detected or retransmitted by UDP itself
- UDP datagram is checksum protected for error detection (remember that IP only protects its header by checksum – why?)
- Error recovery must be implemented by the applications themselves (e.g., by means of a protocol on top of UDP)

UDP datagram structure

0	3						
Source port	Destination port						
Checksum	Length						
Data (variable length)							

Advantages and disadvantages of UDP

- Simple building block with almost 'minimal' design – easy to use as basis for higher-order protocols with maximal design flexibility ^(C)
- Widely implemented as part of the TCP/IP suite of protocols – every computer connected to the Internet can speak UDP too ⁽³⁾
- No reliable delivery or error recovery \otimes
- No flow control mechanisms what happens if one host sends data at a faster rate than the receiving host can cope with? ⁽³⁾

Transmission Control Protocol (TCP)

- TCP is used to establish a bidirectional byte stream between two applications on two hosts (a TCP 'connection')
- The byte stream is created by sending variablelength blocks of bytes in a series of TCP segments. At most one TCP segment per IP datagram
- Applications are identified by their respective port numbers
- Byte stream is reliable errors and missing data are detected and retransmission is requested
- Flow control mechanisms enable better utilisation of available bandwidth

TCP datagram structure



TCP sequence numbers

- TCP uses a sliding window protocol, with a variable window size. Sequencing is by a byte sequence count.
- The sequence number is the sequential number of the first byte of this segment. (The very first byte is given a *random* sequence number.)
- The acknowledgement number is the number of the next byte which the receiver expects. It acknowledges all preceding bytes of the data stream. This field is used only if the ACK flag is set
- Note that if the acknowledgement from one segment is lost, a later acknowledgement may well replace it, with no error seen

The Header Length is the length of the TCP header, in 32-bit 'words,' of all the options field(s), OR is the offset, in words, where the payload (data) starts.

TCP flags

There are six TCP flag bits:

- SYN Synchronise sequence numbers, especially for start-up
- ACK Acknowledgement number is valid
- FIN Finish of byte stream, i.e. close connection (in *one* direction)
- RST Reset the connection
- PSH Data so far is to be forwarded immediately, TCP shouldn't wait before sending it (not very useful these days)
- URG Urgent pointer field is valid (almost never used)

TCP window and checksum

Receive Window

 Used for flow control, it tells how many bytes can be received beyond those acknowledged. The sender knows how many it has actually sent when it receives the acknowledgement, and therefore how many beyond that can still be received. The receiver may vary the window size.

Checksum

 Take the 1-s complement sum of the segment (as 16bit words) and store its complement as the checksum. (The checksum includes a 32-bit 'pseudo- header' including the IP addresses, protocol and length)

TCP Connection Protocol

- TCP uses a modified 3-way handshake, to guard against lost or duplicated packets or segments.
 [Shay 2nd edition pp 522-523, pp 36-37 or 3rd edition p 578]
- On the diagram we use an Initial sequence number of 1. Actual sequence numbers are chosen at random, *not starting from 1!*



TCP Disconnection Protocol

 Again, use a modified 3-way handshake, to guard against lost or duplicated packets or segments



How TCP achieves reliability

- Two mechanisms: checksum in each datagram and sequence numbering of bytes with acknowledgement
- Each datagram contains a sequence number for its first payload byte. Missing datagrams are detected by a sequence number that is too high compared to the number of bytes actually received
- Received bytes are acknowledged by returning the expected sequence number of the next expected byte to the sender, with the ACK flag set
- Sender resends unacknowledged bytes after a certain timeout
- Checksum detects errors in TCP datagrams datagram is dropped at receiver and correction is done by retransmission

Example: Acking TCP datagrams – no error*

- .
- Host A -> Host B: 100 bytes, SEQ 13456
- Host B -> Host A: ACK, expect SEQ 13556 (=13456 + 99 other bytes + 1) to come next
- Host A -> Host B: 200 bytes, SEQ 13556
- Host B -> Host A: ACK, expect SEQ 13756 (=13556 + 199 other bytes + 1) to come next
- Host A -> Host B: 120 bytes, SEQ 13756
- Host B -> Host A: ACK, expect SEQ 13876 (=13756 + 119 other bytes + 1) to come next

* Host A sending data to Host B, simplified

Example: Acking TCP datagrams – with error*

- ...
- Host A -> Host B: 100 bytes, SEQ 13456
- Host B -> Host A: ACK, expect SEQ 13556 (=13456 + 99 other bytes + 1) to come next
- Host A -> Host B: 200 bytes, SEQ 13556 (this is lost)
- Host A -> Host B: 120 bytes, SEQ 13756
- Host B -> Host A: ACK, expect SEQ 13556 to come next
- Host A expects acknowledgement with expected Seq 13876. This is not coming, Host A times out and resends from the last acknowledged byte:
- Resend: Host A -> Host B: 200 bytes, SEQ 13556
- Host B -> Host A: ACK, expect SEQ 13876 (=13756 + 119 other bytes + 1) to come next
 - * Host A sending data to Host B, simplified

Why datagrams may be lost

- Dropped at an overloaded router (too many datagrams in the router's queue)
- Corrupted by bit errors due to noise or interference – dropped at the receiver because checksum doesn't compute to correct value
- Dropped at the receiver because the receiver cannot process the data at the required rate and its buffers are full

TCP Congestion Control

- Size of TCP's sliding window is varied to control sending rate
- TCP's sending window is usually called its congestion window
- TCP senses congestion by observing *lost* packets, by watching sequence numbers
- When congestion occurs, the congestion window size is halved – exponential backoff
- TCP then increases the congestion window again, one segment at a time

ICMP – Internet Control Message Protocol

Provides support for IP. ICMP packets have an 8-bit message type, e.g.:

• **Destination Unreachable** (routing failure)

0	4	8 12	16	20	24	28		
	TYPE (3)	CODE (0)	CHECKSUM					
UNUSED – MUST BE ZERO								
IP HEADER + FIRST 64 BITS OF DATAGRAM								

• *Echo Request or Reply* (PING to remote station)

0 4	8	12	16	20	24	28		
TYPE (8 or 0)) C	ODE (0)		CHECKSUM				
IDENTIFICATION				SEQUENCE NUMBER				
OPTIONAL DATA								

ping and traceroute

Well-known applications for simple network testing

- *ping* lets you check whether a remote machine is reachable and how long it takes to get a reply
- *ping* is often misused for denial-of-service attacks these days. Many firewalls will drop ping packets
- traceroute is like ping, except that it will also show you all hosts along the route
- *tracert* under Windows
- If a TCP or UDP port on a host is unused, incoming connection requests / UDP packets are answered with an ICMP 'Port unreachable' message

SSH - Secure SHell protocol

- ssh is an application that uses SSH to provide remote login to Internet hosts over TCP via port 22
- Provides some terminal emulation (like *telnet*)
- All data between ssh client and remote host is encrypted
- Several different mechanisms to authenticate users (without having to send passwords in clear)
- Can run other protocols (e,g, file transfer) through an ssh tunnel

FTP – File Transfer Protocol

- Mother of all download protocols!
- Carried over TCP, specification in RFC 959



FTP commands

- open <host>
- quit

open FTP connection to <host>

lls [<dir>] local list local change of directory lcd <dir> [<dir>] S remote list cd remote change of directory <dir> • get <file> download file download several files <filemask> mget put <file> upload file <filemask> mput upload several files enter binary mode enter ASCII mode (converts line breaks а automatically between different platforms)