



# COMPSCI 101 Principles of Programming

Lecture 24 - Using the Python interpreter, Python sequences

3

- ▶ Sequence types
- ▶ There are five types of sequences in Python. In CompSci 101 we use three of these: **strings**, **lists** and **tuples**.
- ▶ Sequences allow you to store multiple values in an organized and efficient fashion.
- ▶ The indices of the elements of a sequence start at 0. The indices can be negative (to access elements from the end of the sequence).
- ▶ The order of the elements in a sequence is important.
- ▶ Each element of a sequence can be accessed using square brackets and the index number, e.g.,

```
a_tuple = (3, 4, 8)
print(a_tuple[2])
middle = a_list[1]
last = a_string[-1]
```



## Sequences: strings, lists and tuples



## Learning outcomes

- ▶ At the end of this lecture, students should be able to:
  - ▶ recognise sequences and the common features of sequences
  - ▶ use the interactive Python interpreter to check python statements and functions
  - ▶ use the interactive Python interpreter to look up Python help

2



## Sequences continued

▶ Sequences can be sliced:

```
a_tuple = (3, 4, 8, 7, 2)
a_list = [3, 4, 8, 0, 1]
a_string = "3and 4"
a_tuple2 = a_tuple[0:3:2]
a_list2 = a_list[1:3]
print(a_tuple2, a_list2, a_string[5:1:-2])
```

(3, 8) [4, 8] 4d

- ▶ The **len()**, **min()**, **max()** functions can be applied to sequences (**sum()** can be used with tuples and lists).

```
a_tuple_list = [(3, 'c'), (9, 'a'), (1, 'z')]
print(len(a_tuple))
print(len(a_string))
print(max(a_tuple))
print(max(a_string))
print(len(a_tuple_list))
print(len(a_string_list))
```

```
5
6
8
n
3
(9, 'a')
```

4

3

```
word = "wonderful"
number = 0
for letter in word:
    if letter in "aeiou":
        number += 1
print(number)
```

- ▶ A for ... in ... loop is used to visit each character in a string sequence. The elements of a string sequence are the characters making up the string.



## Iterating through the elements of strings

```
a_tuple = (3, 4, 8, 7, 2)
a_list = [3, 4, 8, 24, 1]
total = 0
for number in a_tuple:
    total += number
print("1.", total)

total = 0
for number in a_list:
    total += number
print("2.", total)
```

1.24

2.40

- ▶ A for ... in ... loop can be used to visit each element of a sequence, e.g.,



## Iterating through the elements of sequences

```
def get_num_uniques(a_sequence):
    uniques = []
    for
        if
            uniques.
    return len(uniques)

def main():
    words = "Number of unique elements:"
    print(words, get_num_uniques("green apple"))
    print(words, get_num_uniques("abcde1g"))
    print(words, get_num_uniques("abbbbbb"))
    print(words, get_num_uniques(3, 4, 3, 3, 4, 6, 3, 7, 8, 4))
    print(words, get_num_uniques([3, 4, 3, 3, 4, 6, 3, 7, 8, 4]))
    print(words, get_num_uniques([3, 4, 3, 3, 4, 6, 3, 7, 8, 4]))
main()
```

```
Number of unique elements: 8
Number of unique elements: 7
Number of unique elements: 2
Number of unique elements: 5
Number of unique elements: 5
```

- ▶ Complete the get\_num\_uniques() function which returns the number of unique elements in the sequence (including non alphabetic characters).



## Iterating through the characters of a sequence – Exercise 1

```
a_tuple = (3, 4) * 3 + (2, 1)
a_list = [3, 0, 1] + [6, 2] * 2
a_string = "3 & 4" * 2 + "end"
print(a_tuple)
print(a_list)
print(a_string)
print(4 not in a_tuple, 24 in a_list, "23" in a_string)
```

False False False

```
(3, 4, 3, 4, 3, 4, 2, 1)
[3, 0, 1, 6, 2, 6, 2]
3 & 43 & 4end
```

## Sequences continued



- ▶ The +, \*, and 'in' operators can all be used with sequences

## Iterating through the characters of a string – Exercise 2



- ▶ Complete the `count_longer_words()` function to find the count of words that are longer than the parameter word from a given list of words.

```
def count_longer_words(a_list, word):
    count = 0
    for
        if
            return count

def main():
    print(count_longer_words(['Double', 'letters', 'in', 'green', 'apple'], 'go'))
    print(count_longer_words(['Number', 'of', 'unique', 'elements'], 'go'))

main()
```

4  
3

9

## Compilers and interpreters



- ▶ **Compilers**
  - ▶ Compilers convert source code into machine code and store the machine code in a file. The machine code can then be run directly by the operating system as an executable program (... .exe file).
- ▶ **Interpreters**
  - ▶ Interpreters bypass the compilation process and convert and execute the code directly statement by statement.
  - ▶ Python is an interpreted language, i.e., the Python interpreter reads and executes each statement of the Python source program statement by statement:
  - this is why even if you can have an error in the program further down, the program executes until it hits that error.

11

## Iterating through the characters of a string – Exercise 3



- ▶ Complete the `count_doubles()` function which returns the number of double letters (a letter followed by the same letter) excluding double spaces, in the string passed as a parameter.

```
def count_doubles(text):
    ...
    count = 0

def main():
    print("Double letters in green apple", count_doubles("green apple"))
    print("Double letters in abcdefg", count_doubles("abcdefg"))
    print("Double letters in abbbb", count_doubles("abbbb"))

main()
    Double letters in green apple 2
    Double letters in abcdefg 0
    Double letters in abbbb 3
```



10

## Python IDLE



- ▶ **IDLE (Integrated Development Environment)** is an integrated development environment provided when you download Python.
- ▶ **WIKIPEDIA** states "IDLE is intended to be a simple IDE and suitable for beginners, especially in an educational environment. To that end, it is cross-platform, and avoids feature clutter."

IDLE provides an interactive environment for checking Python code and for running Python programs.



12



▶ The interactive Python interpreter

- ▶ The Python interactive interpreter makes it easy to **check** Python commands.
- ▶ Open the interactive interpreter
- ▶ We will use IDLE which opens a window with the interpreter prompt: >>>

- ▶ Once the Python interpreter has started any Python command can be executed (at the prompt >>>)

Notice that the interpreter displays the result of each statement even though there is no print() in the statement

```
>>> word = "amazing"
>>> len(word)
7
>>> word = word * 3
>>> word
'amazingamazingamazing'
>>> another_word = word[2:3]
>>> another_word
'a'
>>> 'amlaazg'
'amlaazg'
>>> word[:0:-4]
'gaml'
```



The Python interactive interpreter help



- ▶ The interactive Python interpreter can also be used to get help:

```
>>> help(str.find)
find(...)
    S.find(sub[, start[, end]] -> int
    Return the highest index in S where substring sub is found,
    such that sub is contained within S[start:end]. Optional
    arguments start and end are interpreted as in slice
    notation.
    Return -1 on failure.

>>> help(sum)
sum(...)
    sum(iterable[, start]) -> value
    Return the sum of an iterable of numbers (NOT strings) plus
    the value of parameter 'start' (which defaults to 0). When
    the iterable is empty, return start.
```



- ▶ The interactive Python interpreter can also be used to test functions
- ▶ The Python interactive interpreter makes it easy to check Python code.

```
>>> def get_result(command, what_to_do, where):
    return command + " " + what_to_do + " in the " + where

>>> get_result("a", "p", "c")
'a b in the c'
>>> get_result("come", "sing", "hall")
'come sing in the hall'
>>> get_result("go", "jump", "pond")
'go jump in the pond'
```

See the results of calling the function three times with different arguments.

Notice that it is necessary to insert a blank line to end the function definition.



- ▶ print statements (in the interpreter window) just print to the interpreter window.
- ▶ A function which does not explicitly return a value, always returns None.



```
>>> def do_little(n1, n2):
    print("Sum:", n1 + n2)

>>> do_little(3, 5)
Sum: 8
>>> print(do_little(3, 5))
Sum: 8
>>> do_little(3, 5)
None
```

Notice that it is necessary to insert a blank line to end the function definition.

The code in the function executes.

The result of calling the function is printed.



## Summary

- ▶ strings, lists and tuples are sequences
- ▶ The operators: +, \* and in can be used with sequences
- ▶ We use a for ... in ... to iterate through each element of a sequence
- ▶ len(), min(), max() can be used with sequences
- ▶ sum() can be used with tuples and lists
- ▶ Each element of a sequence can be accessed using the index operator.
- ▶ The index can be negative (starting from the end of the sequence)
- ▶ Sequences can be sliced using [slice\_start: slice\_end: step]
- ▶ The Python interactive interpreter (IDLE)
- ▶ use the interactive Python interpreter to check python statements and functions
- ▶ use the interactive Python interpreter to look up Python help